

EG4 CHARGEVERTER 5KW AC CHARGER

The EG4 Chargeverter is a powerful 48V battery charger capable of rapidly charging at 100 amps, or more than 5000 watts, significantly faster than traditional chargers.

48V Nominal Battery Voltage

3 Year Warranty*


100A Max Charging Current

120Vac or 240Vac Input Capability

Optimized for 240Vac power supplies for maximum output. 120Vac needs an adapter cable, not included. (For 120Vac plug pinout, see our user manual.)

Built-In Breaker

This unit has a built-in breaker to quickly shut off the charger output for added safety and protection.



Optimal For Use with a Generator

Plug your Chargeverter directly into a generator to charge batteries without concern for generator power quality issues, commonly referred to as dirty power."

*Only when used indoors

| Charger Output Specifications | |
|-------------------------------|--|
| Battery Voltage | 48Vdc nominal |
| Charge Current (adjustable) | 0-100A (0-50A at 120V) |
| Charge Voltage (adjustable) | 43-57dc (default 54Vdc) |
| Max Output Watts | 5120W at 240Vac, 3050W at 120Vac |
| Max Efficiency | 94% at 240Vac, 92% at 120Vac |
| AC Input Specifications | |
| AC Input Voltage Range | 90-264Vac |
| AC Frequency | 50-60Hz |
| Maximum Input Amps | 26A at 240Vac, 28A at 120Vac |
| Environmental Specifications | |
| Operating Temperature Range | 14°F to 131°F (-10°C to 55°C) |
| Humidity | 5% to 95% relative humidity (non-condensing) |
| Rating | IP21 |
| Operating Altitude | 0~1500 m (0~4921 ft.) |
| General Specifications | |
| Dimensions H×W×D | 4.5×13.8×4.7 in. (11.5×35.0×12.0 cm) |
| Net Weight | 16.4 lbs. (7.4 kg) |
| Warranty | 3 years |

