

Enphase S230 Microinverter

Built on the fifth-generation platform, the **Enphase S230 Microinverter™** achieves the highest inverter efficiency for module-level power electronics. With its all-AC approach, the S230 simplifies design and installation for 230 VA installations, and delivers optimal energy harvest. The S230 is compatible with storage systems, including battery management systems.

The Enphase S230 integrates seamlessly with the Enphase Envoy-S™ communications gateway, and Enphase Enlighten™ monitoring and analysis software.



Productive

- Maximizes energy production
- Minimizes impact of shading, dust, and debris

Simple and Reliable

- No GEC needed for microinverter
- No DC design or string calculation required
- More than 1 million hours of testing
- Industry-leading warranty, up to 25 years

Advanced Grid Ready

- Complies with fixed power factor, voltage and frequency ride-through requirements
- Remote updating to respond to changing grid requirements
- Configurable for variable grid profiles like Hawaiian Electric Company (HECO) Rule 14H, California Rule 21



To learn more about Enphase offerings, visit enphase.com

Enphase S230 Microinverter

INPUT DATA (DC)		S230-60-LL-2-US	
Commonly used module pairings ¹	195 W - 285 W		
Maximum input DC voltage	48 V		
Peak power tracking voltage	27 V - 37 V		
Operating range	16 V - 48 V		
Min/Max start voltage	22 V / 48 V		
Max DC short circuit current	15 A		
OUTPUT DATA (AC)		208 VAC	240 VAC
Peak output power	230 VA	230 VA	
Maximum continuous output power	220 VA	220 VA	
Nominal voltage/range ²	208 V / 183-229 V	240 V / 211-264 V	
Nominal output current	1.06 A	0.92 A	
Nominal frequency/range	60 / 57 - 61 Hz	60 / 57 - 61 Hz	
Extended frequency range	57 - 63 Hz	57 - 63 Hz	
Power factor at rated power	1.0	1.0	
Maximum units per 20 A branch circuit	25 (three phase)	17 (single phase)	
Maximum output fault current	663 mA rms, 100 ms	663 mA rms, 100 ms	
Power factor (adjustable)	1 / 0.7 leading ... 0.7 lagging	1 / 0.7 leading ... 0.7 lagging	
EFFICIENCY		208 VAC	240 VAC
CEC weighted efficiency	96.5 %	97.0 %	
Peak inverter efficiency	96.7 %	97.2 %	
MECHANICAL DATA			
Ambient temperature range	-40°C to +65°C		
Connector type	MC4-compatible locking		
Dimensions (WxHxD)	172 mm x 175 mm x 35 mm (without bracket)		
Weight	1.8 kg (4 lbs)		
Cooling	Natural convection - No fans		
Enclosure environmental rating	Outdoor - NEMA 6		
FEATURES			
Compatibility	60-cell PV modules		
Communication	Power line		
Integrated ground	The DC circuit meets the requirements for ungrounded PV arrays in NEC 690.35. Equipment ground is provided in the Engage Cable. No additional GEC or ground is required. Ground fault protection (GFP) is integrated into the microinverter.		
Monitoring	Enlighten Manager and MyEnlighten monitoring options		
Compliance	UL1741/IEEE1547, FCC Part 15 Class B, CAN/CSA-C22.2 NO. 0-M91, 0.4-04, and 107.1-01 This product is UL Listed as PV Rapid Shut Down Equipment and conforms with NEC-2014 and NEC-2017 section 690.12 and C22.1-2015 Rule 64-218 Rapid Shutdown of PV Systems, for AC and DC conductors, when installed according manufacturer’s instructions.		

1. Suggestion only, inverter self limits DC inputs.

2. Nominal voltage range can be extended beyond nominal if required by the utility.

To learn more about Enphase offerings, visit enphase.com